


CATALOGUE &gt; Release 8.7

CONNECTION &gt; Series 6000 super-rapid fittings

## Fittings Mod. 6950

Junction




## DIMENSIONS

| Mod.           | G  | L    | Weight (g) |
|----------------|----|------|------------|
| <b>6950 4</b>  | 4  | 32.5 | 3          |
| <b>6950 6</b>  | 6  | 35.5 | 4          |
| <b>6950 8</b>  | 8  | 40.5 | 7          |
| <b>6950 10</b> | 10 | 46   | 10         |
| <b>6950 12</b> | 12 | 48   | 13         |
| <b>6950 14</b> | 14 | 52   | 17         |

## Fittings Mod. 6555

Junction Elbow



## DIMENSIONS


| Mod.              | A  | G  | C   | L    | F    | T    | M    | SW | Weight (g) |
|-------------------|----|----|-----|------|------|------|------|----|------------|
| <b>6555 4-4</b>   | 4  | 4  | 3.5 | 22   | 9    | 16.5 | 17.5 | 9  | 8          |
| <b>6555 6-6</b>   | 6  | 6  | 4   | 24.5 | 12.7 | 18   | 20   | 9  | 14         |
| <b>6555 8-8</b>   | 8  | 8  | 5   | 27.5 | 14.2 | 20   | 22.5 | 11 | 21         |
| <b>6555 10-10</b> | 10 | 10 | 5.8 | 32   | 16.5 | 23   | 26   | 13 | 26         |

## Fittings Mod. 6708

Protection caps

Colour: Black

Self-extinguishing material, class V0



## DIMENSIONS

| Mod.           | A  | F    | L    | Weight (g) |
|----------------|----|------|------|------------|
| <b>6708 4</b>  | 4  | 10.7 | 10.7 | 1          |
| <b>6708 5</b>  | 5  | 11.7 | 11   | 1          |
| <b>6708 6</b>  | 6  | 13.7 | 11.5 | 1          |
| <b>6708 8</b>  | 8  | 15.7 | 12.5 | 1          |
| <b>6708 10</b> | 10 | 18.5 | 13   | 1          |
| <b>6708 12</b> | 12 | 20.7 | 15   | 2          |
| <b>6708 14</b> | 14 | 23.7 | 15   | 2          |